



ORIGINALS


New Generation Flooring

SPC FLOORING

With 0.30-0.50 Wear Layer

Technical Datasheet

DECOR	PACKAGE	PALETTE	CONTAINER
PLANK 	 9 Pieces = 2.503 m ² = 20,38 kg	 44 Package = 110,151 m ² = 916,61 kg	 30 Palette = 3.304,53 m ² = 27.498,33 kg
DECOR	PACKAGE	PALETTE	CONTAINER
HERRINGBONE 	 16 Pieces = 1.800 m ² = 14,65 kg	 56 Package = 100,800 m ² = 840,40 kg	 30 Palette = 3.024,00 m ² = 25.212 kg

Production Identification		AREA SPC FLOOR	
Surface Integrity Test		Embossed In Register / Microbevel	
Construction		Vinyl decor with SPC core, pre-attached IXPE and scratch coating	
Material - Core		Endure Core SPC - Stone Polymer Composite 2000 kg/m ³ density	
Protection		Ultimate Shield, Scratch, Stain and Wear Resistant - Surface Coating	
Surface Treatment		UV	
Usage		Residential - Commercial	
Warranty Period		0.30 Wear Layer: Residential 15 years - Commercial 3 years 0.50 Wear Layer: Residential 20 years - Commercial 7 years	
Joint		Uniclic for Plank / Unidrop for Herringbone	
Installation Method		Were fixed mechanically to the substrate	1 mm - 1,5 mm (Kg/m ³ 100)
Underlay		IXPE	1 mm - 1,5 mm (Kg/m ³ 100)

General Requirements	EN16511	0.30 mm Wear Layer Specification	0.50 mm Wear Layer Specification
Total Thickness	 EN 17539	0.30 mm	0.50 mm
Wear Layer Thickness	 EN 17539	4+1 and 5+1 and 5+1,5 mm	
Length	 EN 17539	610-750-1220-1520-1524-1820 mm.	
Width	 EN 17539	120-150-182-228-305 mm.	
Length and Width of Squared Elements	 EN 17539	pass	pass
Squareness	EN 17539	≤0.20 mm	≤0.20 mm
Straightness	 EN 17539	≤0.30 mm	≤0.30 mm
Flatness Crosswise	EN 17539	concave ≤0.15% convex ≤0.20%	concave ≤0.15% convex ≤0.20%
Flatness Lenghtwise	EN 17539	concave ≤0.50% convex ≤1%	concave ≤0.50% convex ≤1%
Openings	EN 17539	average ≤0.15 mm max ≤0.20 mm	average ≤0.15 mm max ≤0.20 mm
Height Difference	EN 17539	average ≤0.10 mm max ≤0.15 mm	average ≤0.10 mm max ≤0.15 mm
Dimensional Stability and Curl	 EN 23999	≤0.15 mm %1 ≤2 mm	≤0.15 mm %1 ≤2 mm

Classifaction Surface Performance	EN16511	0.30 mm Wear Layer Specification	0.50 mm Wear Layer Specification
Class	 EN ISO 10874	Class 23-31-32	Class 23-31-32-33-34
Wear Resistance Method A - Taber Test	 EN 24338	Class 32	Class 34
Micro Scratch Resistance (Class) For Mat Surfaces (Gloss)	 TSE CEN/TS 16611	Class 32	Class 34
Impact Resistance (big ball)	 EN 13329:2006+A1:2008 Annex F	Class 32	Class 34
Castor Chair Test	 EN ISO 4918	Class 32	Class 34
Effect of Furniture Leg	 ISO 16581, tested with foot type 0]	Class 32	Class 34
Residual Indentation	 EN ISO 24343-1	Class 32	Class 34
Resistance to Staining	 EN438-2 +A1	Grade for group 1,2,3	Grade for group 1,2,3
Flexibility Categories	 EN ISO 178:2019	High rigidity	High rigidity
Light Fastness	 EN ISO 105-B02:2014	≥6	≥6
Locking Strength (kN/m)	 ISO 24334	Class 32	Class 34

Product Performance - Physical Behaviour	EN14041	0.30 mm Wear Layer Specification	0.50 mm Wear Layer Specification
Slide Resistance 	TS EN 13893	DS	DS
Fire Behavior 	TS EN 13501-1	Bfl S1	Bfl S1
Thermal Resistance 	ISO 8302	0,0311 M2k/w	0,0311 M2k/w
Thermal Conductivity 	EN 12667	0,296 W/(m.K)	0,296 W/(m.K)
Floor Heating System 	suitable	max 27	max 27
Electrostatics Behaviour 	EN 1815:2016	antistatics floor covering	antistatics floor covering

Enviroment	EN14041	0.30 mm Wear Layer Specification	0.50 mm Wear Layer Specification
Emission of Forhaldehyde 	EN 717-1:2004	E1	E1
Antibacterial 	ISO22196	Pass	Pass
Phatalate Analysis 	Inhouse Method	Phatalate Free	Phatalate Free
VOC Emissions Class - (French Regulation) 	French VOC Regulation	A+	A+
VOC Emission - Indoor Air Comfort Gold 	French VOC Regulation	E1	E1
VOC Emission - M1 	M1 Protocol of November 2017	Pass	Pass

More VOC Test



European Directive Limiting the VOC Concent in Certain Products, 2004/42/EC

FloorScore® Standard
Indoor Air quality Certified to SCS-105 Version 4.2 - 2023

Pass

AREA FLOORS PRODUCTION : Ömerli Mahallesi, Ilgaz Sokak, No: 7/1, Arnavutköy, İstanbul / Türkiye

AREA FLOORS EUROPE : Gietijzerstraat 20 3534AV Utrecht The Netherlands

T : +90 (212) 741 51 61 info@areafloors.com.tr

www.areafloors.com.tr



TS EN 14761+A1



EN ISO 16511



100% Recycled



ISO 9001:2015



ISO 14001:2015



ISO 45001:2018



ORIGINALS

New Generation Flooring

SPC FLOORING

WITH 0.30-0.50 WEAR LAYER TECHNICAL DATASHEET